



Technical Data

grandMA2 full-size

Technical Data	
Operating Voltage	120 V / 230 V
Supply Voltage	50 / 60 Hz (automatic detection)
Net weight	46 kg / 101 lbs
Power	350 VA
Dimensions	1,284 x 204 x 661 mm / 50.6 x 8 x 26 inches
Output Connectors	6 x XLR 5pin (DMX)
	2 x DVI (external monitor)
	2 x etherCON
	1 x MA Link (grandMA2 fader wing)
	5 x USB
	1 x DIN (MIDI)
Input Connectors	2 x XLR 4 pin (desklight)
	1 x XLR 5pin (DMX)
	1 x XLR 3pin (Sound)
	1 x XLR 3 pin (SMPTE)
	1 x DIN (MIDI)
	1 x Sub-D 25pol (Analog Remote)
	1 x powerCON

grandMA2 light

Technical Data	
Operating Voltage	120 V / 230 V
Supply Voltage	50 / 60 Hz (automatic detection)
Net weight	37 kg / 81.6 lbs
Power	350 VA
Dimensions	935 x 204 x 652 mm / 36.8 x 8 x 25.7 inches
Output Connectors	6 x XLR 5pin (DMX)
	2 x DVI (external monitor)
	2 x etherCON
	1 x MA Link (grandMA2 fader wing)
	5 x USB
	1 x DIN (MIDI)
	2 x XLR 4 pin (desklight)



Input Connectors	1 x XLR 5pin (DMX)
	1 x XLR 3pin (Sound)
	1 x XLR 3 pin (SMPTE)
	1 x DIN (MIDI)
	1 x Sub-D 25pol (Analog Remote)
	1 x powerCON

grandMA2 ultra-light

Technical Data	
Operating Voltage	120 V / 230 V
Supply Voltage	50 / 60 Hz (automatic detection)
Net weight	30 kg / 66.1 lbs
Power	350 VA
Dimensions	935 x 204 x 652 mm / 36.8 x 8 x 25.7 inches
Output Connectors	6 x XLR 5pin (DMX)
	2 x DVI (external monitor)
	2 x etherCON
	1 x MA Link (grandMA2 fader wing)
	4 x USB
	1 x DIN (MIDI)
	2 x XLR 4 pin (desklight)
Input Connectors	1 x XLR 5pin (DMX)
	1 x XLR 3pin (Sound)
	1 x XLR 3pin (SMPTE)
	1 x DIN (MIDI)
	1 x Sub-D 25pol (Analog Remote)
	1 x powerCON

grandMA2 replay unit (RPU)

Technical Data	
Operating Voltage	120 V / 230 V
Supply Voltage	50 / 60 Hz (automatic detection)
Net weight	11.3 kg / 25 lbs
Power	150 VA
Dimensions	485 x 445 x 126 mm / 19 x 17.5 x 5 inches



Output Connectors	6 x XLR 5pin (DMX)
	2 x DVI (external monitor)
	2 x etherCON
	1 x MA Link (grandMA2 fader wing)
	3 x USB
	1 x DIN (MIDI)
	2 x XLR 4pin (desklight)
Input Connectors	1 x XLR 5pin (DMX)
	1 x XLR 3pin (Sound)
	1 x XLR 3pin (SMPTE)
	1 x DIN (MIDI)
	1 x Sub-D 25pol (Analog Remote)
	1 x powerCON

grandMA2 fader wing

Technical Data	
Operating Voltage	120 V / 230 V
Supply Voltage	50 / 60 Hz (automatic detection)
Net weight	4.5 kg / 9.9 lbs
Power	40 VA
Dimensions	365 x 395 x 70 mm / 14.4 x 15.6 x 2.8 inches
Output Connectors	4 x XLR 5pin (DMX)
	2 x USB
Input Connectors	1 x USB

MA onPC command wing

Technical Data	
Operating Voltage	120 V / 230 V
Supply Voltage	50 / 60 Hz (automatic detection)
Net weight	6 kg / 13.2 lbs
Power	40 VA
Dimensions	540 x 400 x 75 mm / 21.3 x 15.7 x 3 inches



Output Connectors	2 x XLR 5pin (DMX)
	1 x USB
	1 x DIN (MIDI)
Input Connectors	1 x XLR 5pin (DMX)
	1 x XLR 3pin (SMPTE)
	1 x DIN (MIDI)
	1 x Sub-D 15pol (Analog Remote)
	1 x IEC 60320 C13 / C14 (IEC cord)

MA onPC fader wing

Technical Data	
Operating Voltage	120 V / 230 V
Supply Voltage	50 / 60 Hz (automatic detection)
Net weight	4.5 kg / 9.9 lbs
Power	40 VA
Dimensions	365 x 395 x 70 mm / 14.4 x 15.6 x 2.8 inches
Output Connectors	4 x XLR 5pin (DMX)
	2 x USB
Input Connectors	1 x USB